



Structural Baseline & Dynamic Core System Summary

The core system architecture centers on a dual-chamber free-piston hydraulic compressor and pump unit. It replaces a traditional crankshaft assembly with direct linear transmission, coupling chemical combustion force directly to high-pressure fluid output.

Immutable Core Engine Parameters:

- **Engine Core Weight:** 23.0 lbs encased in a high-strength Duplex 2205 structural steel housing.
- **Peak Continuous Output:** 500 Watts (0.67 HP) operating at a standard 60 BPM (1.0 Hz) cycle frequency.
- **Cruising Pulse Rate:** 19.2 BPM idle frequency (one fire cycle every 3.1 seconds) to maintain low acoustic and thermal tracking signatures in wilderness environments.
- **PCfire (Combustion Cylinder) Geometry:** 3.5-inch bore diameter with a 2.6-inch total cycle stroke.
- **PChyd (Hydraulic Pump Cylinder) Geometry:** 2.6-inch bore diameter with a 2.6-inch total stroke.
- **Solid Driving Transmission Rod:** 0.75-inch solid cylindrical shaft connecting the two high-pressure faces.
- **Inertial Acceleration Matrix:** A compact, high-density 600-gram pure tungsten insert embedded directly behind the steel crown of the PCfire piston to bridge the work-energy expansion deficit.

System Operating Pressures & Direct Fluid Loops:

- **Hydraulic Accumulator Threshold:** Maintains a locked constant resistance of **20 atmospheres (293.92 PSI)** via an active spring-loaded displacement piston.
 - **Peak Combustion Pressure Target:** Holds a flat **12.0 atm (176.40 PSI)** and **385°F** constant-temperature isobaric push during the controlled fuel injection window (0.00" to 1.20" displacement) before transitioning to an adiabatic coast from 1.20" to 2.60" BDC.
 - **The Closed Anatomy Loop:** High-pressure fluid travels from the accumulator out through the **Aorta** to fuel multi-axis joint cylinders and electrical motor-generators. Spent, low-pressure fluid aggregates into a common return line—the **Vena Cava**—which passes directly back into the intake check valve of the PChyd pump, creating a completely sealed fluid recirculation matrix.
-



Structural Architecture & Total Material Volume Matrix

The platform weight and dimensional matrix are rigorously audited using volumetric tracking across all primary structural components. This mathematically bridges the gap between raw 3D CAD geometries (measured in volumetric displacement) and true, physical scale-weight performance.

1. Volumetric Blueprint Allocations (Excel Ledger Audit):

The skeletal and structural component space is mapped across major moving and stationary zones, calculating the exact volume displacement required for fabrication:

- **Right Plus Left Legs, Ankles, Feet, & Pelvis: 336.8209 cubic inches** (5,519.5 cc).
- **Thorax and Head Assembly: 115.9292 cubic inches** (1,899.73 cc).
- **Right Shoulder Structure: 67.5356 cubic inches** (1,106.71 cc).
- **Left Shoulder Structure: 67.5356 cubic inches** (1,106.71 cc).
- **Right Forearm Assembly: 41.0400 cubic inches** (672.52 cc).
- **Left Forearm Assembly: 41.0400 cubic inches** (672.52 cc).
- **Total Whole-Robot Material Displacement: 669.9013 cubic inches** ($(10,977.69 \text{ cubic centimeters})$).

2. Polymeric Materials Variant Weights (PLA vs. PETG Scaling):

By utilizing this fixed whole-robot displacement volume (10,977.69 cc), the structural weight of an ultra-lightweight, 3D-printed rapid-prototyping variant scales directly based on material density constants:

- **PLA Plastic Profile (Density = 1.24 g/cm³):**
 $(10,977.69 \text{ cc}) \times 1.24 \text{ g/cm}^3 = 13,612.33 \text{ grams}$
 Converting to Imperial standard mass yields a structural shell weight of **30.01 lbs.**
- **PETG Plastic Profile (Density = 1.27 g/cm³):**
 $(10,977.69 \text{ cc}) \times 1.27 \text{ g/cm}^3 = 13,941.67 \text{ grams}$
 This equates to a raw structural mass profile of **13.94 Kilograms**, which converts directly to a finalized shell weight of **30.66 lbs.**

3. Duplex 2205 Stainless Steel Tibia Geometry

For heavy-duty tactical field variants, the structural bone matrix upgrades to a double-channel H-beam truss arrangement:

- **Cross-Sectional Column Area: 0.9179 square inches.**
- **Ultimate Yield Strength:** The sub-1-inch cross-section allows the lower leg structural bones to safely withstand **60,000 pounds (30 tons)** of pure vertical crushing force before experiencing any physical deformation.
- **The Thin-Leg Spatial Clearance:** Centering the linear hydraulic cylinder thrust along the core vertical axis allows the lower limb profile to remain exceptionally narrow. This ensures one ankle sweeps cleanly past the opposite ankle in a straight-line human-mimicking gait, eliminating the wide, un-athletic "waddle" of traditional electric motor robots.



Articulated Tripod Footprint & Follower Link Decoupling

The lower leg connects to a fully articulated terrain adaptation matrix designed to stabilize a 198-lb combat load on unimproved, crumbling mountain steps without relying on power-hungry software stabilization loops.

- **The 3-Toe Dynamic Tripod Layout:** The base contact plate features a segmented tripod consisting of a wide medial big toe, a lateral little toe, and an identical heavy matching heel block. Each independent digit houses a dual-cylinder connection: one cylinder serves as an inline, fluid-bypass passive shock absorber to soak up high-impact alpine terrain shocks, while its partner acts as a CPU-driven active positioning actuator to claw into loose stone or deliver propulsion force.
 - **The Mechanical Follower Link:** To resolve the geometric conflict between bending a foot up and down (plantar/dorsi flexion) and tilting it side-to-side (inversion/eversion), a custom physical follower arm linkage isolates the kinematics.
 - **Kinematic Decoupling Logic:** The follower arm dynamically shifts the mounting anchor point of the twin gold-capped ankle leveling cylinders along a perfect matching arc during a stride. As the foot pushes off its toes, this mechanical linkage handles the vector calculation physically, ensuring that up-and-down movement cannot cross-talk or alter the side-to-side inversion setting. The fluid remains perfectly trapped inside the tilting cylinders for **zero electrical processing overhead** and zero accidental shifting.
-



Auxiliary Power Distribution & Sentry Mode Metrics

Energy conversion is governed by a split-tier auxiliary power architecture that mimics a biological metabolism, alternating between extreme energy-density sleep states and full-power mechanical operation.

The Passive Valve Clamping Loop (The WOW Metric):

To achieve an efficient **147 Mechanical Watts** cruising consumption rate at a steady 2.0 MPH, the robot utilizes **Passive Hydraulic Valve Clamping**. The moment a limb finishes a step and establishes a firm surface stance, the high-pressure fluid valves seal shut, locking the cylinders into rigid steel pillars. The platform supports its full vertical mass against gravity using **zero continuous electrical current**, only drawing accumulator pressure during active 38-inch strides or 3-inch vertical step lifts.

Dual-Tier Power Generation Loops:

1. **The Standby Sentry Loop (Hibernation Metabolism):** When standing motionless on watch, all large-displacement muscle cylinders are isolated and locked. The main 500W engine stays cold and dark. A miniature, low-volume fluid line feeds a **baby hydraulic motor** that spins a **baby generator**, trickling a trace 10 to 15-watt current into a **baby battery buffer** to keep low-frequency VLF radio ears and local

sensor cameras active. This tier consumes a microscopic **27.0 grams of diesel fuel every 72 hours**, requiring the free-piston core to wake up and execute just one single, isolated heartbeat stroke every ~1.8 hours.

2. **The Active Combat Loop (Full Engagement Metabolism):** The instant a local sensor trips, the CPU brings the **large-displacement hydraulic motor/generator setup** online. The main free-piston engine instantly scales from zero up to its 19.2 BPM cruising loop or its 90 BPM sprint frequency, flooding the aorta with high-pressure fluid to engage natural, high-velocity kinematics.
-